












OZNACZENIE NA RYSUNKU		Dz1	Dz2	D1	D2	Dk	Dp	Dt1	Dt2	
										
WYMIARY OTWORU W MURZE (mm)	S ₀	2000	900	900	900	900	1150	2700	1800	
	H ₀	2270	2070	2070	2070	2070	2070	2200	2200	
SZEROKOŚĆ DRZWI Z OŚCIEŻNICĄ (mm)	S _Z	1980	880	880	880	880	1130	2680	1780	
WYSOKOŚĆ SKRZYDŁA Z GÓRNĄ BELKĄ OŚCIEŻNICY (mm)	H _Z	2250	2050	2050	2050	2050	2050	2180	2180	
IL. SZTUK	PRZYZIEMIE	1L	1P	1P+1L	1L	1P	1	1	1	
	PODDASZE			2P+1L	1L					
ILOŚĆ SZTUK OGÓŁEM		13								
UWAGI		DRZWI ZEWNĘTRZNE	DRZWI WEWNĘTRZNE			min EI30	drzwi przesuwne	DRZWI TARASOWE	DRZWI TARASOWE	

OZNACZENIE NA RYSUNKU		01	02	0P
				
WYMIARY OTWORU W MURZE (mm)	S ₀	1200	900	—
	H ₀	1350	1500	—
SZEROKOŚĆ OKNA Z OŚCIEŻNICĄ (mm)	S _Z	1165	835	780
WYSOKOŚĆ SKRZYDŁA Z GÓRNĄ BELKĄ OŚCIEŻNICY (mm)	H _Z	1285	1435	1600
IL. SZTUK	PRZYZIEMIE	3		
	PODDASZE		2	8
ILOŚĆ SZTUK OGÓŁEM		13		
UWAGI		ZASTOSOWAĆ OKNA Z FUNKCJĄ MIKROWENTYLACJI	OKNO DACHOWE	